



Demolition Grabs

Simplify Your Demolition and Sorting

Multipurpose Tool that Increases Demolition Efficiency

Full 360° Hydraulic Rotation

Comprehensive Dealer Network Providing Sales, Parts and Service, and Backed by the Industry's Best Support!



NPK ATTACHMENTS DESIGNED, BUILT & BACKED BY NPK

SPECIFICATIONS

NPK Model	Recommended Carrier Weight (lb-metric tons)	Weight* (lb-kg)	Capacity (Volume) (yd ³ -L)	Operating Pressure (psi-bar)	Oil Flow (gpm-lpm)	Closing Force (lbf-kN)	Rotation		Dimensions		
							Operating Pressure (psi-bar)	Oil Flow (gpm-lpm)	A (in-mm)	B (in-mm)	C (in-mm)
DG-4	5,500 - 9,000 lb	380 lb	0.12 yd ³	2,610-3,770 psi	4 - 9 gpm	3,370 lbf	1,500-2,000 psi	3-6 gpm	45 in	33 in	18 in
	2.5 - 4 metric tons	172 kg	90 L	180-260 bar	15 - 35 lpm	15 kN	100-140 bar	12-22 lpm	1,145 mm	837 mm	450 mm
DG-4EH	5,500 - 9,000 lb	455 lb	0.12yd ³	2,610-3,770 psi	4 - 9 gpm	3,370 lbf	1,500-2,000 psi	3-6 gpm	45 in	33 in	18 in
	2.5 - 4 metric tons	206 kg	90 L	180-260 bar	15 - 35 lpm	15 kN	100-140 bar	12-22 lpm	1,145 mm	837 mm	450 mm
DG-6	9,000 - 13,000 lb	640 lb	0.2 yd ³	2,900-4,060 psi	5 - 10 gpm	4,720 lbf	1,450-1,885 psi	2.5-4 gpm	53 in	41 in	20 in
	4 - 6 metric tons	290 kg	150 L	200-280 bar	20 - 40 lpm	21 kN	100-130 bar	10-15 lpm	1,355 mm	1,045 mm	500 mm
DG-6EH	9,000 - 13,000 lb	715 lb	0.2 yd ³	2,900-4,060 psi	5 - 10 gpm	4,720 lbf	1,450-1,885 psi	2.5-4 gpm	53 in	41 in	20 in
	4 - 6 metric tons	325 kg	150 L	200-280 bar	20 - 40 lpm	21 kN	100-130 bar	10-15 lpm	1,355 mm	1,045 mm	500 mm
DG-9	11,000 - 20,000 lb	990 lb	0.24 yd ³	3,190-4,640 psi	8 - 13 gpm	7,195 lbf	1,450-1,885 psi	3-4 gpm	64 in	43 in	23 in
	5 - 9 metric tons	450 kg	180 L	220-320 bar	30 - 50 lpm	32 kN	100-130 bar	12-15 lpm	1,632 mm	1,080 mm	580 mm
DG-9EH	11,000 - 20,000 lb	1,065 lb	0.24 yd ³	3,190-4,640 psi	8 - 13 gpm	7,195 lbf	1,450-1,885 psi	3-4 gpm	64 in	43 in	23 in
	5 - 9 metric tons	485 kg	180 L	220-320 bar	30 - 50 lpm	32 kN	100-130 bar	12-15 lpm	1,632 mm	1,080 mm	580 mm
DG-14	15,000 - 31,000 lb	1,415 lb	0.39 yd ³	3,625-5,075 psi	8 - 16 gpm	8,540 lbf	1,450-2,030 psi	5-8 gpm	71 in	46 in	28 in
	7 - 14 metric tons	642 kg	300 L	250-350 bar	30 - 60 lpm	38 kN	100-140 bar	20-30 lpm	1,800 mm	1,175 mm	700 mm
DG-16	22,000 - 35,000 lb	1,930 lb	0.56 yd ³	3,625-5,075 psi	16 - 26 gpm	10,790 lbf	1,450-2,030 psi	5-8 gpm	72.8 in	48.6 in	34 in
	10 - 16 metric tons	875 kg	425 L	250-350 bar	60 - 100 lpm	48 kN	100-140 bar	20-30 lpm	1,850 mm	1,235 mm	860 mm
DG-20A	31,000 - 44,000 lb	2,755 lb	0.65 yd ³	3,625-5,075 psi	16 - 26 gpm	11,690 lbf	1,450-2,030 psi	8-13 gpm	80.7 in	51.2 in	37 in
	14 - 20 metric tons	1,250 kg	500 L	250-350 bar	60 - 100 lpm	52 kN	100-140 bar	30-50 lpm	2,050 mm	1,300 mm	950 mm
DG-25	35,000 - 57,000 lb	3,200 lb	0.78 yd ³	3,625-5,075 psi	16 - 26 gpm	11,690 lbf	1,450-2,030 psi	8-13 gpm	85 in	52 in	44 in
	16 - 26 metric tons	1,450 kg	600 L	250-350 bar	60 - 100 lpm	52 kN	100-140 bar	30-50 lpm	2,160 mm	1,330mm	1,115 mm
DG-30A	40,000 - 66,000 lb	4,080 lb	1.05 yd ³	3,625-5,075 psi	21 - 32 gpm	16,185 lbf	1,450-2,030 psi	8-13 gpm	94.9 in	58.6 in	44 in
	18 - 30 metric tons	1,850 kg	800 L	250-350 bar	80 - 120 lpm	72 kN	100-140 bar	30-50 lpm	2,410 mm	1,490 mm	1,115 mm
DG-40A	55,000 - 88,000 lb	4,520 lb	1.18 yd ³	3,625-5,075 psi	21 - 32 gpm	16,185 lbf	1,450-2,030 psi	8-13 gpm	94.9 in	58.6 in	54 in
	25 - 40 metric tons	2,050 kg	900 L	250-350 bar	80 - 120 lpm	72 kN	100-140 bar	30-50 lpm	2,410 mm	1,490 mm	1,360 mm
DG-50	77,000 - 110,000 lb	5,510 lb	1.44 yd ³	3,625-5,075 psi	26 - 37 gpm	20,230 lbf	1,450-2,320 psi	8-13 gpm	96.5 in	61 in	57 in
	35 - 50 metric tons	2,500 kg	1,100 L	250-350 bar	100 - 140 lpm	90 kN	100-160 bar	30-50 lpm	2,450 mm	1,560 mm	1,450 mm

Specifications reflect standard configurations: single motor DG-4/4EH, DG-6/6EH, DG-9/9EH, DG-14, DG-16 and double motor DG-20A, DG-25, DG-30A, DG-40A, DG-50. *Weight does not include mounting bracket. Specifications subject to change without notice.

360° Rotation Allows for Easy Repositioning:

Full Hydraulic

» Equipped with a full hydraulic rotation system which requires a secondary hydraulic circuit

Optional Electro-Hydraulic: "EH" Models

» Equipped with an electro-hydraulic selector valve allowing operation for both jaw and rotation off of a single auxiliary circuit and 12V power connection

Fully-protected hose routing

Pilot check valve prevents unexpected opening of arms

Main pin integrated with dust seals



Easy Maintenance
High-strength and wear-resistant Hardox® steel

Bolt-on bracket for versatility

Powerful hydraulic rotation motor featuring dual motors for DG-20A through DG-50, ideal for heavy-duty high-torque applications

Protected cylinder with cushion at end of the opening

Cutting tips are interchangeable and reversible for extended wear life

Each product sold by NPK is subject to an express written warranty. NPK makes no other warranty, express or implied, including any warranty of merchantability or fitness for any particular purpose. NPK is not liable for any incidental or consequential damages.



Scan for more information on Demolition Grabs

NPK Construction Equipment, Inc.

7550 Independence Drive
Walton Hills, OH 44146-5541
Phone (440) 232-7900

